



General notes for information purposes only

Note 1

1. Approximately 500 linear feet boardwalk in total
2. Boardwalk construction to be American Disabilities Act (ADA) compliant (<http://www.usdoj.gov/crt/ada/reg3a.html#Anchor-19425>) and to follow Francis Bay, National Park Service design
3. Boardwalk elevation no greater than 3 feet
4. Typical boardwalk width 4 feet
5. Boardwalk entrance and egress to be ramped with an ADA compliant slope.
6. Handrails, edges, etc to be ADA compliant
7. No construction to take place in wetland
8. Deck material may consist of wood or recycled, weather-durable plastic

Note 2

1. Footpath to consist of existing bed material
2. Approximately 65 linear feet of plants to be installed
3. Plant installation on outer edge (road side) of path only
4. Prior to planting, holes to be excavated to 1.5 times depth of root ball
5. Backfill hole with weed-free soil

Note 3

1. No construction or excavation to take place in wetland
2. If necessary, platforms to be cantilevered
3. Platform to be located at maximum boardwalk elevation
4. Typical platform dimension 4' x 8'
5. Platform location to be adjusted in the field where pond view is maximized
6. Platform to be located where wetland width is minimal

Note 4

1. Existing chain link fence to be recessed around platform

Note 5

1. Island to be constructed from two to many logs
2. Branches of logs not to be removed
3. Logs minimum 15 feet long, 10 inch diameter
4. Logs tied together with salt-water resistant chain or similar material
5. Logs to be floated into place and anchored to pond bottom with concrete blocks or similar weight

Note 6

1. Ten (10) white mangrove (*Laguncularia racemosa*) seedlings to be planted where needed in Location A.
2. Ten (10) black mangrove (*Avicennia germinans*) seedlings to be planted where needed in Location B.

